

V Rod Jug Huggers ***'Performance Pipes with a Twist'***

BUB's new Jug Hugger pipes are the best of all worlds. Stepped header technology for optimum performance. Fat, bigger than life removable heat shields for a macho look that will never blue, and a stylish twist at the end for a cool look finished with a chrome billet tip. All this and a removable inner chamber which can run with baffles, torque chambers or open. See what all the talk is about...

INSTALLATION

The first step is to remove your stock exhaust system. ***The 02 sensor must be removed from the front header before the header is removed.*** You must also remove the stud from the rubber bushing that attaches the rear header. (***note: we recommend replacing the exhaust gaskets to insure a proper seal at the port.***) Offer the front pipe to the head and install flange nuts finger tight. Insert two of the 5/16 x 3/4" hex bolts into the rear slotted bracket of the front header. Install the 4-hole mounting plate over the bolts in a ***horizontal*** position with the remaining holes in the plate facing above the header. Install a flat washer and nylok nut over each bolt leaving finger tight for now.

Next, with a flat washer installed over each, insert two 5/16 x 1" hex bolts (1 each) through the mounting tabs of the front header (through the top). Insert the two .250 aluminum spacers (1 each) over the bolts, and insert the bolts through the stock mounting bar. (***note: It may be necessary to move the mounting bar into alignment first.***) Back with flat washers and nylok nuts leaving finger tight.

Offer the rear pipe to the bike and install the flange nuts finger tight. Insert two 5/16 x 3/4" hex bolts into the rear slotted bracket of the header and install into the remaining two holes of the 4-hole mounting plate. Back each with a flat washer and nylok nut.

Align the front pipe and tighten the entire front header assembly. Repeat procedure with rear header. ***Reinstall the 02 sensor into the front header.*** Align and tighten heat shield clamps.

DETAILS, DETAILS

Clean the pipes thoroughly before firing as grease or fingerprints will become permanent with heat! We use a quality glass cleaner and a clean, soft cloth. Check all fasteners after the first ride, and again at all service intervals.

Thank you for buying a BUB!

BUB ENTERPRISES 180 Spring Hill Dr., Grass Valley, CA 95945
Ph (530) 477 7490 (800) 934 9739 Fax (530) 477 7489
www.bub.com