



## TOOLS REQUIRED

- 10mm & 14mm Sockets
- 12mm box/end wrench
- 3/8" Ratchet and 6" extension
- Torque wrench

## ITEMS SUPPLIED

- **MIKADO** Exhaust Silencer
- Spacer
- 8mm x 20mm bolt (x4)
- 8mm x 45mm bolt (x1)
- Instruction #SB39-000013

## PLEASE NOTE

Our warranty applies only when the system is installed correctly and used for its intended purpose. Warranty does not apply when damage is the result of normal wear and tear, improper use, neglect or incorrect engine configuration. See warranty notice in box for more information.

## CONTACT US

BUB ENTERPRISES, INC.  
180 Spring Hill Drive  
Grass Valley, CA 95945  
Phone 800.934.9739  
www.bubtech@bubent.com

## Installation Instructions

## SUZUKI GSXR Bolt On MIKADO Slip-On Silencer

System part number  
SB12-1003/1004/1005

Thank you for buying a MIKADO Slip-on Silencer. We are committed to providing you a quality product that with the proper installation and care will last you for many years to come.

**Please be sure to read the instructions fully and inspect all components of your new system before installation.** If you do not have an understanding of how to remove your stock system, or how to install the MIKADO Slip-on, you should seek the advice and/or skill of a professional mechanic. Please keep all OEM parts as some may be used for the installation of the MIKADO Slip-on.

If you are installing the system and are not the owner, please return these instructions to the owner as they contain important information that may be required at a later date.

If you have questions pertaining to the installation and/or tuning, please contact our technical service department:  
800.934.9739 or e-mail [bubtech@bubent.com](mailto:bubtech@bubent.com)

## Installation Instructions

- Remove the four Silencer retaining nuts and washers.
- Remove the upper Silencer mount bolt and washer, then remove OEM Silencer. Make sure to keep the OEM gasket as it can be reused if in good condition.
- Install MIKADO silencer (make sure to install gasket first) using the supplied 8x20mm bolts and OEM washers. Leave bolts finger tight.
- Install your new MIKADO slip-on silencer using the supplied 0.5" spacer and supplied 8x45mm bolt and OEM nut at the upper mount. NOTE: The 0.5" spacer goes between the inside of silencer bracket and passenger foot peg mount. Tighten to 12-15 lb/ft.

## -----TUNING-----

- Installation of the MIKADO Slip-on will increase performance, for additional increased ride-ability and throttle response a Dynojet Power Commander is recommended.

## -----CLEANING-----

- Never use harsh chemicals or any type of abrasive material to clean the silencer. We recommend only mild detergent and a soft rag.